



ASCENTAC
Fiber Clear

FTTH Fiber Optic Tool Kit

Ascentac KitMate100

FTTH Fiber Optic Tool Kit—Top Choice for Compact and Complete Fiber Splicing & Wiring

Feature

- 6 in 1 full-featured set
- Include power meter and VFL with 10mW
- Time-saving for optical fiber cold splicing


Application

- Maintenance in telecom and CATV
- Test lab of optical fibers
- Other fiber optic measurements

Introduction

Ascentac FiberClear KitMate100 Series, FTTH Fiber Optic Tool Kit, contains a complete set of fiber optic termination tools such as optical power meter, fiber cleaver, drop cable stripper, triple hole fiber optic stripper, alcohol bottle and carrying case.

This tool kit is thoughtfully designed for compact storage and ease of use, making it the perfect solution for fiber optic cold splicing and cabling tasks.



Optical Power Meter

Ascentac FiberGo OPM150 Series, Optical Power Meter, can accurately measure the optical power in fiber optic network, helping technicians ensure optimal network performance.



Fiber Cleaver

Weitech CLV-001, Fiber Cleaver, provides a precise cleave and prepares a fiber to be fusion spliced for 250 μm and 900 μm coated optical fiber.



Drop Cable Stripper

It can strip the outer jacket of drop cables and cuts the strength members to expose the fiber inside.



Triple Hole Fiber Optic Stripper

It can strip fiber optic cables of different types, including loose tube cables and bonded fibers.



Alcohol Bottle

It can store and dispense cleaning fluids, such as isopropyl alcohol, to clean the end-faces of fiber optic cables.



Carrying Case

It can safely store and transport fiber optic tools and accessories, ensuring they are well-organized and protected during handling.



Specification

Optical Power Meter

Power Range (dBm)	+30 to -50
Calibrated Wavelength (nm)	850, 980, 1270, 1300, 1310, 1490, 1550, 1577, 1625, 1650
Accuracy (dB)	± 0.4 @ +23 to -40dBm ± 1.0 @ +23 to +26dBm, -40 to -45dBm ± 3.0 @ +26 to +30dBm, -45 to -50dBm
VFL Wavelength (nm)	650 ± 20
VFL Output Power (mW)	10
Optical Connector	Universal 2.5mm
Power Supply	USB Type C
L x W x H (mm)	35 x 20 x 120
Weight(g)	51

Fiber Cleaver

Cleave Angle (°)	≤ 0.8
Coating Diameter (mm)	0.25mm, 0.9mm
Cleave Length (mm)	9 to 16 (Single Fiber - 0.25mm Coating) 10 to 16 (Single Fiber - 0.9mm Coating)
Blade Life (times)	48000
L x W x H (mm)	60 x 64 x 64
Weight(g)	360

Drop Cable Stripper

Applicable Cable (mm)	3.1 x 2.0
Core	1, 2
Material	ABS & Metal
Temperature (° C)	-20 to 45
L x W x H (mm)	30 x 110 x 20
Weight(g)	100

Triple Hole Fiber Optic Stripper

Fiber Diameter	The biggest hole: 2 to 3mm, optical fiber outer protective layer The middle hole: 0.25 to 0.9mm, white soft rubber protective layer The smallest hole: 0.125 to 0.25mm, coating of optical fiber core
----------------	---

Alcohol Bottle

Capacity (ml)	210
L x W x H (mm)	60 x 60 x 120

Carrying Case

L x W x H (mm)	240 x 130 x 160
----------------	-----------------



© Copyright 2025 Ascentac. All rights reserved. The information in this document is subject to change without notice.

For the latest information regarding this product, please visit our website at <http://www.ascentac.com>



Contact us